

## TAPE AND REEL INFORMATION



### QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| SN74AXCH1T45DBVR | SOT-23       | DBV             | 6    | 3000 | 180.0              | 8.4                | 3.2     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| SN74AXCH1T45DCKR | SC70         | DCK             | 6    | 3000 | 180.0              | 8.4                | 2.3     | 2.5     | 1.2     | 4.0     | 8.0    | Q3            |
| SN74AXCH1T45DRY2 | SON          | DRY             | 6    | 5000 | 180.0              | 9.5                | 1.6     | 1.15    | 0.68    | 4.0     | 8.0    | Q3            |
| SN74AXCH1T45DRYR | SON          | DRY             | 6    | 5000 | 180.0              | 9.5                | 1.2     | 1.65    | 0.7     | 4.0     | 8.0    | Q1            |
| SN74AXCH1T45DTQR | X2SON        | DTQ             | 6    | 3000 | 180.0              | 9.5                | 0.94    | 1.13    | 0.5     | 2.0     | 8.0    | Q2            |

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal

| Device           | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------------|--------------|-----------------|------|------|-------------|------------|-------------|
| SN74AXCH1T45DBVR | SOT-23       | DBV             | 6    | 3000 | 210.0       | 185.0      | 35.0        |
| SN74AXCH1T45DCKR | SC70         | DCK             | 6    | 3000 | 210.0       | 185.0      | 35.0        |
| SN74AXCH1T45DRY2 | SON          | DRY             | 6    | 5000 | 189.0       | 185.0      | 36.0        |
| SN74AXCH1T45DRYR | SON          | DRY             | 6    | 5000 | 189.0       | 185.0      | 36.0        |
| SN74AXCH1T45DTQR | X2SON        | DTQ             | 6    | 3000 | 189.0       | 185.0      | 36.0        |