

TIDA-01012 REV E1 Bill of Materials

Item #	Designator	Quantity	Value	PartNumber	Manufacturer	Description	PackageReference
1	PCB	1		TIDA-01012	Any	Printed Circuit Board	
2	BT1	1		1021	Keystone	HOLDER BATTERY AAA, TH	HOLDER BATTERY AAA, TH
3	C1	1	0.1uF	GRM155R71C104JA88D	MuRata	CAP, CERM, 0.1 µF, 16 V, +/- 5%, X7R, 0402	0402
4	C2, C8, C9, C21, C25, C26, C29, C30, C31, C32, C33, C35, C38, C46, C51, C52, C71	17	0.1uF	CL03A104KP3NNNC	Samsung Electro-Mechanics	CAP, CERM, 0.1 µF, 10 V, +/- 10%, X5R, 0201	0201
5	C3, C4, C24, C28, C36, C47, C55, C58, C65, C66, C72	11	1uF	GRM155R61A105KE15D	MuRata	CAP, CERM, 1 µF, 10 V, +/- 10%, X5R, 0402	0402
6	C5, C27, C39, C68	4	1uF	C1005X5R0J105M050BB	TDK	CAP, CERM, 1 µF, 6.3 V, +/- 20%, X5R, 0402	0402
7	C6	1	22uF	GRM155R60J226ME11D	MuRata	CAP, CERM, 22 µF, 6.3 V, +/- 20%, X5R, 0402	0402
8	C7	1	4.7uF	GRM188R6YA475KE15D	MuRata	CAP, CERM, 4.7 µF, 35 V, +/- 10%, X5R, 0603	0603
9	C10, C11	2	1200pF	C0402C122J5GACTU	Kemet	CAP, CERM, 1200 pF, 50 V, +/- 5%, C0G/NP0, 0402	0402
10	C12	1	0.1uF	C0603C104J5RACTU	Kemet	CAP, CERM, 0.1 µF, 50 V, +/- 5%, X7R, 0603	0603
11	C13	1	10pF	C0603C100F5GAC7867	Kemet	CAP, CERM, 10 pF, 50 V, +/- 1%, C0G/NP0, 0603	0603
12	C14	1	0.01uF	C0805C103F1GACTU	Kemet	CAP, CERM, 0.01 µF, 100 V, +/- 1%, C0G/NP0, 0805	0805
13	C15	1	330pF	GRM1555C1H331FA01J	MuRata	CAP, CERM, 330 pF, 50 V, +/- 1%, C0G/NP0, 0402	0402
14	C16	1	470pF	08055A471FAT2A	AVX	CAP, CERM, 470 pF, 50 V, +/- 1%, C0G/NP0, 0805	0805
15	C17	1	150pF	GRM1555C1H151JA01D	MuRata	CAP, CERM, 150 pF, 50 V, +/- 5%, C0G/NP0, 0402	0402
16	C20	1	2200pF	GRM1885C1H222JA01D	MuRata	CAP, CERM, 2200 pF, 50 V, +/- 5%, C0G/NP0, 0603	0603
17	C22	1	100pF	C1608C0G2A101F080AA	TDK	CAP, CERM, 100 pF, 100 V, +/- 1%, C0G/NP0, 0603	0603
18	C23	1	0.022uF	C1608X7R2A223K	TDK	CAP, CERM, 0.022 µF, 100 V, +/- 10%, X7R, 0603	0603
19	C34, C56, C57	3	4.7uF	C1005X5R1A475K050BC	TDK	CAP, CERM, 4.7 µF, 10 V, +/- 10%, X5R, 0402	0402
20	C40, C41	2	22pF	GCM0335C1E220JD03D	MuRata	CAP, CERM, 22 pF, 25 V, +/- 5%, C0G/NP0, AEC-Q200 Grade 1, 0201	0201
21	C42, C43	2	12pF	GRM0335C1H120JA01D	MuRata	CAP, CERM, 12 pF, 50 V, +/- 5%, C0G/NP0, 0201	0201
22	C48, C53	2	0.47uF	GRM033R60J474KE90D	MuRata	CAP, CERM, 0.47 µF, 6.3 V, +/- 10%, X5R, 0201	0201
23	C49	1	39pF	GRM1555C1H390JA01D	MuRata	CAP, CERM, 39 pF, 50 V, +/- 5%, C0G/NP0, 0402	0402
24	C54	1	2.2uF	GRM155R61C225KE11D	MuRata	CAP, CERM, 2.2 µF, 16 V, +/- 10%, X5R, 0402	0402
25	C59, C62, C64, C67	4	10uF	CL05A106MP5NUNC	Samsung Electro-Mechanics	CAP, CERM, 10 µF, 10 V, +/- 20%, X5R, 0402	0402
26	C63	1	100uF	C3216X5R1A107M160AC	TDK	CAP, CERM, 100 µF, 10 V, +/- 20%, X5R, 1206_190	1206_190
27	D1, D2	2	35V	CDBU0130L	Comchip Technology	Diode, Schottky, 35 V, 0.1 A, SOD-523F	SOD-523F
28	D3	1	-20V	SI2323DS	Vishay-Siliconix	MOSFET, P-CH, -20 V, -3.7 A, SOT-23	SOT-23
29	F1	1		NANOSMDC020F-2	TE Connectivity	Fuse, Resettable, 0.2 A, 24 VDC, SMD	1206
30	FL1	1	2.45 GHz	LFB182G45BG5D920	MuRata	Filter, BandPass, 2.45GHz, SMD	1.6x0.8mm
31	J1	1		66.9040-22	Multi-Contact	MAH561 Connector, XELW-4, Red, THD	XELW-4 Connector, TH
32	J2	1		66.9040-21	Multi-Contact	MAH561 Connector, XELW-4, Black, THD	XELW-4 Connector, TH
33	J3	1		20021121-00006C4LF	FCI	Header, 1.27 mm, 3x2, Au, SMT	Header, 1.27mm, 3x2, SMT
34	J4	1		HFW4R-1STE1LF	Amphenol FCI	CONN FFC BOTTOM 4POS 1.00MM R/A	
35	J5	1		20021121-00010C4LF	FCI	Header, 1.27mm, 5x2, Gold, SMT	Header, 1.27mm, 5x2, SMT
36	J6	1		0473460001	Molex	Connector, Receptacle, Micro-USB Type B, R/A, Bottom Mount SMT	7.5x2.45x5mm
37	L1, L2	2	2.2uH	MLZ2012A2R2WT000	TDK	Inductor, Multilayer, Ferrite, 2.2 µH, 0.21 A, 0.15 ohm, SMD	0805

Item #	Designator	Quantity	Value	PartNumber	Manufacturer	Description	PackageReference
38	L3	1	1500 ohm	BLM18HE152SN1D	MuRata	Ferrite Bead, 1500 ohm @ 100 MHz, 0.5 A, 0603	0603
39	R1, R24	2	13.3k	CRCW040213K3FKED	Vishay-Dale	RES, 13.3 k, 1%, 0.063 W, 0402	0402
40	R2	1	8.2	CRCW04028R20JNED	Vishay-Dale	RES, 8.2, 5%, 0.063 W, 0402	0402
41	R3	1	10.0k	CRCW040210K0FKED	Vishay-Dale	RES, 10.0 k, 1%, 0.063 W, 0402	0402
42	R4, R14	2	3.01k	CRCW04023K01FKED	Vishay-Dale	RES, 3.01 k, 1%, 0.063 W, 0402	0402
43	R5, R15	2	52.3	CRCW040252R3FKED	Vishay-Dale	RES, 52.3, 1%, 0.063 W, 0402	0402
44	R6	1	9.76k	CRCW04029K76FKED	Vishay-Dale	RES, 9.76 k, 1%, 0.063 W, 0402	0402
45	R7	1	100k	RG1005P-104-B-T5	Susumu Co Ltd	RES, 100 k, 0.1%, 0.063 W, 0402	0402
46	R8	1	1.00Meg	CRCW04021M00FKED	Vishay-Dale	RES, 1.00 M, 1%, 0.063 W, 0402	0402
47	R9	1	100Meg	CRCW0603100MJPEAHR	Vishay-Dale	RES, 100 M, 5%, 0.1 W, 0603	0603
48	R10	1	10.0	CRCW040210R0FKED	Vishay-Dale	RES, 10.0, 1%, 0.063 W, 0402	0402
49	R11, R13	2	0	CRCW04020000Z0ED	Vishay-Dale	RES, 0, 5%, 0.063 W, 0402	0402
50	R12	1	10.2k	CRCW040210K2FKED	Vishay-Dale	RES, 10.2 k, 1%, 0.063 W, 0402	0402
51	R16	1	10.0Meg	CRHV1206AF10M0FKE5	Vishay-Dale	RES, 10.0 M, 1%, 0.3 W, 1206	1206
52	R17	1	499k	CRCW0402499KFKED	Vishay-Dale	RES, 499 k, 1%, 0.063 W, 0402	0402
53	R19, R23	2	133k	CRCW0402133KFKED	Vishay-Dale	RES, 133 k, 1%, 0.063 W, 0402	0402
54	R20	1	95.3	CRCW251295R3FKEG	Vishay-Dale	RES, 95.3, 1%, 1 W, 2512	2512
55	R21	1	11.3k	CRCW040211K3FKED	Vishay-Dale	RES, 11.3 k, 1%, 0.063 W, 0402	0402
56	R25	1	0.5	RL0603FR-070R5L	Yageo America	RES, 0.5, 1%, 0.1 W, 0603	0603
57	R26, R27	2	909	CRCW0201909RFKED	Vishay-Dale	RES, 909, 1%, 0.05 W, 0201	0201
58	R28, R30, R31, R32, R51, R52, R53, R54, R56, R57, R58	11	0	MCR01M2PJ000	Rohm	RES, 0, 5%, 0.063 W, 0402	0402
59	R33, R35, R36, R37, R38, R60, R63, R65	8	47.0k	RK73H1HTTC4702F	KOA Speer	RES, 47.0 k, 1%, 0.05 W, AEC-Q200 Grade 0, 0201	0201
60	R34	1	200k	CRCW0402200KFKED	Vishay-Dale	RES, 200 k, 1%, 0.063 W, 0402	0402
61	R39	1	100k	CRCW0201100KFKED	Vishay-Dale	RES, 100 k, 1%, 0.05 W, 0201	0201
62	R40	1	1.00k	CRCW02011K00FKED	Vishay-Dale	RES, 1.00 k, 1%, 0.05 W, 0201	0201
63	R41, R42, R43	3	10.0k	CRCW020110K0FKED	Vishay-Dale	RES, 10.0 k, 1%, 0.05 W, 0201	0201
64	R44	1	10.0k	ERJ-2RKF1002X	Panasonic	RES, 10.0 k, 1%, 0.1 W, 0402	0402
65	R45	1	0.01	WSL0805R0100FEA18	Vishay-Dale	RES, 0.01, 1%, 0.25 W, 0805	0805
66	R46	1	10k	CRCW040210K0JNED	Vishay-Dale	RES, 10 k, 5%, 0.063 W, 0402	0402
67	R47	1	1.15k	CRCW04021K15FKED	Vishay-Dale	RES, 1.15 k, 1%, 0.063 W, 0402	0402
68	R48	1	9.31k	CRCW04029K31FKED	Vishay-Dale	RES, 9.31 k, 1%, 0.063 W, 0402	0402
69	R49	1	5.76k	CRCW04025K76FKED	Vishay-Dale	RES, 5.76 k, 1%, 0.063 W, 0402	0402
70	R50	1	30.1k	CRCW040230K1FKED	Vishay-Dale	RES, 30.1 k, 1%, 0.063 W, 0402	0402
71	R55	1	1.0k	CRCW04021K00JNED	Vishay-Dale	RES, 1.0 k, 5%, 0.063 W, 0402	0402
72	S1, S2	2		GS-113-0043	CW Industries	Switch, Slide, DPDT, On-On, 0.5 A, 125 V, TH	9.65x7.92mm
73	S3	1		B3U-1000P	Omron Electronic Components	SWITCH TACTILE SPST-NO 0.05A 12V	3x1.6x2.5mm
74	U1	1		ADS8885IDRCR	Texas Instruments	18-Bit, 400-kSPS, Serial Interface, microPower, Miniature, True-Differential Input, SAR Analog-to-Digital Converter, DRC0010D	DRC0010D
75	U2	1		REF3325AIDCKTG4	Texas Instruments	30 ppm / degC Drift, 3.9 uA Voltage Reference, -40 to 125 degC, 3-pin SC70 (DCK), Green (RoHS & no Sb/Br)	DCK0003A
76	U3	1		OPA313IDCKR	Texas Instruments	1-MHz, Micro-Power, Low-Noise, RRIO, 1.8-V CMOS OPERATIONAL AMPLIFIER Precision Value Line Series, DCK0005A	DCK0005A
77	U4	1		TS5A3359DCUR	Texas Instruments	1-Ohm SP3T ANALOG SWITCH 5-V/3.3-V SINGLE-CHANNEL 3:1 MULTIPLEXER/DEMULTIPLEXER, DCU0008A	DCU0008A
78	U5	1		OPA2313IDRGR	Texas Instruments	1-MHz, Micro-Power, Low-Noise, RRIO, 1.8-V CMOS OPERATIONAL AMPLIFIER Precision Value Line Series, DRG0008A	DRG0008A
79	U6	1		THS4531IDGK	Texas Instruments	Ultra Low Power, Rail-to-Rail Output, Fully-Differential Amplifier, DGK0008A	DGK0008A
80	U7	1		TPS78230DRVR	Texas Instruments	Single Output LDO, 150 mA, Fixed 3 V Output, 2.2 to 5.5 V Input, with 0.5 uA Quiescent Current, 6-pin SON (DRV), -40 to 125 degC, Green (RoHS & no Sb/Br)	DRV0006A
81	U8	1		TS3A24159DRCR	Texas Instruments	0.3-ohm 2-Channel SPDT Bidirectional Analog Switch Dual-Channel 2:1 Multiplexer and Demultiplexer, DRC0010J	DRC0010J

Item #	Designator	Quantity	Value	PartNumber	Manufacturer	Description	PackageReference
82	U9	1		OPA333AIDCKR	Texas Instruments	17 uA, MicroPower, Precision, Zero Drift CMOS Operational Amplifier, 1.8 to 5.5 V, -40 to 125 degC, 5-pin SOT23 (DCK0005A), Green (RoHS & no Sb/Br)	DCK0005A
83	U10	1		CC2640F128RGZR	Texas Instruments	Ultra low-power ARM Cortex M3 2.4 GHz Radio MCU, Bluetooth Low Energy, RGZ0048A	RGZ0048A
84	U11	1		MSP430FR2532IRGER	Texas Instruments	Mixed-Signal Microcontrollers, RGE0024G	RGE0024G
85	U12	1		479480001	Molex	2.4GHz Antenna, 50 Ohms, SMD	3.14x3.14mm
86	U13	1		LSF0102DQER	Texas Instruments	2-Channel Bidirectional Multi-Voltage Level Translator for Open-Drain & Push-Pull Application, DQE0008A	DQE0008A
87	U14	1		RF430CL330HIRGTR	Texas Instruments	DYNAMIC NFC INTERFACE TRANSPONDER, RGT0016C	RGT0016C
88	U15, U16	2		TPD1E10B06DPYR	Texas Instruments	ESD in 0402 Package with 10 pF Capacitance and 6 V Breakdown, 1 Channel, -40 to +125 degC, 2-pin X2SON (DPY), Green (RoHS & no Sb/Br)	DPY0002A
89	U17	1		LSF0204RUTR	Texas Instruments	4-Bits Bidirectional Multi-Voltage Level Translator for Open-Drain and PushPull Application, RUT0012A	RUT0012A
90	U18	1		TPS3422EGDRYR	Texas Instruments	Low-Power, Push-Button Controllers With Configurable Delay, DRY0006A	DRY0006A
91	U19	1		BQ27426YZFR	Texas Instruments	System-Side Impedance Track Fuel Gauge, YZF0009-C01	YZF0009-C01
92	U20	1		BQ24232RGTR	Texas Instruments	USB Friendly 0.5 A Li+ Charger with Dynamic Power Management, 10.5 V OVP, 4.3 V, -40 to 85 degC, 16-pin QFN (RGT), Green (RoHS & no Sb/Br)	RGT0016C
93	U21, U23	2		TPS62740DSSR	Texas Instruments	360nA IQ Step Down Converter for Low Power Applications, DSS0012A	DSS0012A
94	U24	1		TPS78227DRVR	Texas Instruments	Single Output LDO, 150 mA, Fixed 2.7 V Output, 2.2 to 5.5 V Input, with 0.5 uA Quiescent Current, 6-pin SON (DRV), -40 to 85 degC, Green (RoHS & no Sb/Br)	DRV0006A
95	U25	1		TS5A3166DCKR	Texas Instruments	0.9-Ohm SPST ANALOG SWITCH, DCK0005A	DCK0005A
96	Y1	1		FC-135 32.7680KA-A3	Epson	Crystal, 32.768 KHz, 12.5 pF, SMD	SMD, 2-Leads, Body 3.2x1.5mm
97	Y2	1		FC-12M 32.7680KA-A3	Epson	Crystal, 32.768kHz, 12.5pF, SMD	Crystal 2.05x.6x1.2mm
98	Y3	1		TSX-3225 24.0000MF20G-AC3	Epson	Crystal, 24 MHz, 9 pF, SMD	SMD, 4-Leads, Body 2.65x3.35mm, Height 0.6mm
99	C18, C19	0	DNP	Used in BOM report	Used in BOM Report	Cap, 0402 footprint placeholder	0402
100	C37, C50	0	39pF	GRM1555C1H390JA01D	MuRata	CAP, CERM, 39 pF, 50 V, +/- 5%, C0G/NP0, 0402	0402
101	C44, C45	0	12pF	GRM0335C1H120JA01D	MuRata	CAP, CERM, 12 pF, 50 V, +/- 5%, C0G/NP0, 0201	0201
102	C69	0	1uF	GRM155R61A105KE15D	MuRata	CAP, CERM, 1 uF, 10 V, +/- 10%, X5R, 0402	0402
103	C70	0	2.2uF	CL05A225KQ5NNNC	Samsung	CAP, CERM, 2.2 uF, 6.3 V, +/- 10%, X5R, 0402	0402
104	FID1, FID2, FID3, FID4, FID5, FID6	0		N/A	N/A	Fiducial mark. There is nothing to buy or mount.	Fiducial
105	R29	0	0	MCR01MZPJ000	Rohm	RES, 0, 5%, 0.063 W, 0402	0402
106	R59, R61, R62, R64	0	47.0k	RK73H1HTTC4702F	KOA Speer	RES, 47.0 k, 1%, 0.05 W, AEC-Q200 Grade 0, 0201	0201

IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ("TI") reference designs are solely intended to assist designers ("Designer(s)") who are developing systems that incorporate TI products. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design.

TI's provision of reference designs and any other technical, applications or design advice, quality characterization, reliability data or other information or services does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such reference designs or other items.

TI reserves the right to make corrections, enhancements, improvements and other changes to its reference designs and other items.

Designer understands and agrees that Designer remains responsible for using its independent analysis, evaluation and judgment in designing Designer's systems and products, and has full and exclusive responsibility to assure the safety of its products and compliance of its products (and of all TI products used in or for such Designer's products) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to its applications, it has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any systems that include TI products, Designer will thoroughly test such systems and the functionality of such TI products as used in such systems. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

Designers are authorized to use, copy and modify any individual TI reference design only in connection with the development of end products that include the TI product(s) identified in that reference design. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of the reference design or other items described above may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS AND OTHER ITEMS DESCRIBED ABOVE ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNERS AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS AS DESCRIBED IN A TI REFERENCE DESIGN OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

TI's standard terms of sale for semiconductor products (<http://www.ti.com/sc/docs/stdterms.htm>) apply to the sale of packaged integrated circuit products. Additional terms may apply to the use or sale of other types of TI products and services.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2016, Texas Instruments Incorporated